

# SYSTEM **KAN-therm**

Innovative water  
and heating solutions



## Novopress Press Tool **ACO203XL**

### Ladies and Gentleman

We have the pleasure to inform You that we have introduced new tools for assembly of **KAN-therm Steel**, **KAN-therm Inox** and **KAN-therm Preess LBP** systems.

### Technical characteristics:



Diameter range	12 – 108mm
Crimping force	32kN
Piston stroke	40 / 80mm (adjustable – 2 steps)
Length	460mm
Height	113mm
Width	83mm
Weight	3.9kg with battery
Device power	450W
Power supply	18V battery
Battery type	18V Li-Ion 3.0Ah
Battery operating time	up to 250 clamps*
Battery charging time	about 60 minutes
Battery status	LED indicator in the button
Additional options	Bluetooth, working with the Novocheck App

TECHNOLOGY OF SUCCESS





## Novocheck application:

The Novocheck application connects the press tool with a smartphone or tablet, making it possible to monitor on a regular basis the status of the tool and the connections made:

- device working time,
- remaining battery charge,
- tool temperature,
- press cycle counter,
- analysis of the correctness of connections made,
- recording the individual events in the device log.

## ACO203XL assembly method:

Drive	ACO203XL Press Tool with Bluetooth + 2x battery 18V Li-Ion 3.0Ah + charger 230V + case: code 1948267181							
Diameter	Jaw		Adapter		Steel	Inox	Steel Sprinkler	Inox Sprinkler
	Type	Code	Type	Code				
[mm]	Type	Code	Type	Code				
12	Jaw M12 type PB2	1948267134	-	-				
15	Jaw M15 type PB2	1948267135	-	-				
18	Jaw M18 type PB2	1948267137	-	-				
22	Jaw M22 type PB2	1948267139	-	-				
28	Jaw M28 type PB2	1948267141	-	-				
35	Jaw M35 type PB2	1948267143	-	-				
	Collar jaw HP35 type PSL Snap On	1948267124						
42	Collar jaw M42 type PSL Snap On	1948267119	ZB203	1948267000	+		-	-
	Collar jaw HP42 type PSL Snap On	1948267126						
54	Collar jaw M54 type PSL Snap On	1948267121	ZB203	1948267000	+		-	-
	Collar jaw HP54 type PSL Snap On	1948267128						
66,7	Collar jaw M66,7 type PSL Snap On	1948267089	ZB221	1948267005				
76,1	Collar jaw M76,1 type PSL Snap On	1948267145						
88,9	Collar jaw M88,9 type PSL Snap On	1948267044						
108	Collar jaw M108 type PSL Snap On	1948267038	ZB221	1948267005				
			ZB222	1948267007				

**!** The diameter of 108 mm should be pressed in 2 stages (first with ZB221 adapter and second with ZB222 adapter) using the same jaw!



**KAN Sp. z o.o.**

ul. Zdrojowa 51, 16-001 Białystok-Kleosin  
tel. +48 85 74 99 200, fax +48 85 74 99 201  
e-mail: kan@kan-therm.com

TECHNOLOGY OF SUCCESS



[www.kan-therm.com](http://www.kan-therm.com)

ISO 9001