

National Declaration of Performance

Number: 61/KAN-DWU/22E

System KAN-therm Inox fittings

Page 1 of 2

1. Name and trade name of building product:

System KAN-therm Inox fittings made of stainless steel 1.4401, 1.4404 [Ø12-168,3 mm]

2. Designation type of building product:

System KAN-therm Inox fittings.

3. Intended use or uses:

For use in indoor installations:

- hot and cold utility water
- · compressed air
- chilled water, heat pumps
- other listed in KAN technical literature in accordance with the "Designer and contractor's guide" issued by KAN Sp. z o.o., the catalog of the KAN-therm System and the guidelines of the KAN Technical Department.
- 4. Name and address of the producer and place of manufacture:

KAN Sp. z o.o.

Zdrojowa 51 PL-16-001 Białystok-Kleosin

Poland

www.kan-therm.com e-mail: kan@kan-therm.com

5. Name and address of the authorized representative:

Not applicable

6. National system used for assessment and verification of performance constancy:

System 3 and 4

- 7. National technical specification:
 - 7a. Polish product standard:

Not applicable.

7b. National technical assessment:

National Technical Assessment ITB-KOT-2019/1106 edition 3 - KAN-therm Inox and KAN-therm Steel pressed connectors for joining steel pipes.

Name of the accredited laboratory and accreditation number:

ITB Warsaw – accreditation No AC 020.



National Declaration of Performance

Number: 61/KAN-DWU/22E

System KAN-therm Inox fittings

Page 2 of 2

8. Declared performance:

Essential characteristics of the construction product for the intended use or uses	Declared performance	Remarks
Geometrical features	Dimension According to ITB-KOT-2019/1106 w. 3	
Material	stainless steel Inox 1.4401; 1.4404 O-rings: EPDM	
Mechanical properties	Maximum working pressure: a / up to 16 bar - for joints pressed with standard tools for diameters Ø12-168,3 mm b / up to 25 bar - for joints pressed with HP tools for diameters Ø12-108 mm For compressed air: a/ diameters to 54 – 16 bar b/diameters over 54 – 10 bar Joint tightness in accordance with ITB-KOT-2019/1106 e. 3	
Physical properties	Temperature range -35 °C to 135 °C (EPDM)	
Reaction to fire	Class A1	
Marking	Accordance to: ITB-KOT-2019/1106 e. 3	
Impact on drinking water	Approved for contact with drinking water.	Hygienic certificate B-BK-60210-1514/21 PCA accreditation No. AB 509 PZH

9. The performance of the product described above is in accordance with all of the declared performance characteristics mentioned in point 8. This national declaration of performance is issued in accordance with the Act of 16 April 2004 regarding construction products, under the sole responsibility of the manufacturer.

On behalf of manufacturer signed by:

Manager of the Quality Assurance Department

Kleosin – 10.05.2022 (place – date of issue)

Janusz Żukowski (signature)