	National declaration of performance	Number: 133/KAN-DWU/25E
	<p>KAN-therm PERT 5W PE-RT Type II pipes with EVOH</p>	<p>Strona 1 z 2</p>

1. Name and trade name of building product:

KAN-therm PERT 5L PE-RT Type II pipes with EVOH

2. Designation type of building product:

KAN-therm PERT 5L PE-RT Type II pipes with EVOH

3. Intended use or uses:

For use in indoor installations of cold and hot utility water, drinking water, central radiator and underfloor heating and installations using glycol water solutions in accordance with the "Designer's and contractor's guide" issued by KAN Sp. z o.o., the catalog of the KAN-therm System and the guidelines of the KAN Technical Department.

4. Name and address of the producer and place of manufacture:

KAN Sp. z o.o.
 Zdrojowa 51 PL-16-001 Białystok-Kleosin
 Poland
www.kan-therm.com e-mail: kan@kan-therm.com

5. Name and address of the authorized representative, if appointed: Not applicable

6. National system used for assessment and verification of performance constancy:

System 3

7. National technical specification:

7a. Polish product standard:


PN-EN ISO 21003-2:2009/A1:2011- Multilayer piping systems for hot and cold water installations inside buildings - Part 2: Pipes.

Name of the accredited laboratory and accreditation number:

SKZ - Testing GmbH, akredytacja DAkkS nr D-PL-19033-01-00

7b. National technical assessment:

Not applicable.

	National declaration of performance	Number: 133/KAN-DWU/25E
	KAN-therm PERT 5W PE-RT Type II pipes with EVOH	Strona 2 z 2

8. Declared performance:

Essential characteristics of the construction product for the intended use or uses	Declared performance	Remarks
Geometric features	Accordance to KAN specifications and PN-EN ISO 21003-2:2009	
Mechanical properties	Design internal pressure resistance determined in accordance with PN-EN ISO 21003-2:2009/A1:2011 For pipes: 12x2, 14x2, 18x2,5, 25x3,5, 32x4,4 Class 2/10 bar ; class 5/10 bar For pipes 16x2 Class 2/10 bar; class 5/8 bar For pipes 17x2 Class 4/6 bar; class 5/6 bar For pipes 18x2 Class 2/10 bar; class 5/8 bar For pipes 20x2 Class 2/8 bar; class 5/6 bar	
Physical properties	Thermal stability : $T_{max} = 90\text{ °C}$ ($T_{mal} = 100\text{ °C}$)	
Marking	Accordance to: PN-EN ISO 21003-2:2009/A1:2011	
Reaction to fire	Class F	
Impact on drinking water	Approved for contact with drinking water	Hygienic certificate PZH B.BK.60210.0710.2025 , PCA accreditation Nr AB 509

9. The performance of the product described above is in accordance with all of the declared performance characteristics mentioned in point 8. This national declaration of performance is issued in accordance with the Act of 16 April 2004 regarding construction products, under the sole responsibility of the manufacturer.

On behalf of manufacturer signed by:

Manager of the Quality Assurance Department

Kleosin – 19.08.2025
(place – date of issue)


Janusz Żukowski
(signature)